



HL168DA

FEATURES:

- 30 memory x 3 users (90 memory total)
- Accurate & precise
- Easy-to-read, wide angle display
- Simple one touch operation
- Smooth & fast measurement

SPECIFICATIONS

Model number	HL168DA
Measurement method	Oscillometric
Measurement range	Pressure: 0 ~ 300 mmHg, Pulse: 40 ~ 199 beats/minute
Accuracy	Pressure: ± 3 mmHg, Pulse: $\pm 5\%$ Max.
Inflation	Automatic inflation (air pump)
Deflation	Automatic air release control valve
Display	Liquid Crystal Display
Memory	30 memory x 3 users (90 memory total)
Unit dimensions	L x W x H: 72 x 70 x 29 mm (2.83 x 2.76 x 1.14 inch)
Unit weight	109.7 \pm 5 g (3.87 \pm 0.17 oz) (Excluding batteries)
Cuff size	135 ~ 195 mm (5.3 ~ 7.7 inch)
Storage/Transportation environment	Temperature: -20 ~ 70°C (-4 ~ 158°F), Humidity: $\leq 90\%$ R.H.
Operation environment	Temperature: 10 ~ 40°C (50 ~ 104°F), Humidity: 15% ~ 90% R.H.
Power supply	Two AAA (1.5V) alkaline batteries
Battery life	Approx. 250 measurements
Auto power off	1 minute after last button operation
Accessories	Instruction manual, 2 AAA alkaline batteries, Storage case

These specifications are subject to change without notice for purpose of improvement.